

## **PIXMA** iP4600



Superior prints and functionality for the best in home photo and document printing

Canon's range-topping A4 PIXMA inkjet printer makes creating beautiful, longlasting prints quick and easy, with extra media-handling features for added versatility.

The PIXMA iP4600 is part of the Canon inkjet Photo & Document Home Printer range.

The Photo & Document Home Printer range consists of: **PIXMA iP4600**, PIXMA iP3600, PIXMA iP2600, PIXMA iP1900 Embargo Date: Sales Start Date: Target Market: 26th August 2008 Mid-September 2008 Creative Connectors/Achievers

## **Key Features in Importance Order:**

- Photolab-quality borderless 10x15cm print in approximately 20 seconds\*
- High-resolution photo printing with 9600x2400dpi, 1pl FINE print engine\*
- 5 Single Inks for more efficient ink usage
- Super-stylish, low-profile design
- Beautiful, long-lasting photos with ChromaLife100<sup>+</sup> system\*\*
- Auto duplex for automatic double-sided printing
- Versatile media handling: two-way paper feeding for different paper types
- Print directly onto DVDs and CDs
- Easy photo correction and red-eye reduction using Easy-PhotoPrint EX software
- No need for a PC: print directly from a digital camera with PictBridge

Product Name	Mercury Code	EAN Code	<b>Recommended Retail Price</b>
PIXMA iP4600	2909B008AA	4960999576930	£89.00 / €116.79

What's in the box:

PIXMA iP4600, Power cord, Print Head, Consumables PGI-520 Bk, CLI-521 Bk, CLI-521 C, CLI-521 M, CLI-521 Y, Multilingual set up guides, Setup software & User's manual CD including Easy-PhotoPrint EX, Media Sales Brochure, Maxell Printable CD/DVD Brochure, Sample Media PP-201 10x15cm (3 sheets), MP-101 A4 (2 sheets) for Head Alignment, Warranty sheet

<sup>\*</sup> See specifications

<sup>\*\*</sup> See www.canon-europe.com/chromalife100



## **PIXMA** iP4600



Consumables	Mercury Code	EAN Code	Recommended retail price
PGI-520 Bk	2932B001AA	4960999577456	£8.99 / €11.99
CLI-521 Bk	2933B001AA	4960999577470	£7.99 / €10.99
CLI-521 C	2934B001AA	4960999577494	£7.99 / €10.99
CLI-521 M	2935B001AA	4960999577517	£7.99 / €10.99
CLI-521 Y	2936B001AA	4960999577531	£7.99 / €10.99

Note: Blister packs with and without security are available for each of the inks listed above

## **Technical Specifications**

Printer functions		Interface and software		
Print Resolution	Up to 9600 <sup>1</sup> x 2400 dpi	(continued)		
Print Engine	InkJet 5-ink with minimum 1 pl ink droplets & FINE print head	Driver Features	Photo Optimizer PRO (Windows only), Image Optimizer (Windows only), Photo Noise Reduction, Vivid Photo	
Photo Lab Quality Speed	Borderless 10 x 15cm: Approx. 20 seconds (Standard)	Software Included	Windows: Easy-PhotoPrint EX,	
Mono Print Speed	Up to 26ppm (Max.), 12.8ppm (Standard)		Mac: Easy-PhotoPrint EX	
Colour Print Speed	Text & Graphics: Up to 21ppm (Max.), 11.2ppm (Standard)	General features		
Ink Cartridge Configuration	Single Ink technology - 5 separate ink tanks (PGI-520BK, CLI-521BK, CLI-521C, CLI-521M, CLI-521Y)	Power Source Power Consumption	AC 100-240V, 50/60Hz Standby: Approx. 1.3W	
Black Ink Tank Life	Black Ink Tank Life Black: 350 pages (PGI-520BK), 1875 pages* (CLI-52BK) <sup>2</sup> Black: 3160 photos* (PGI-520BK),		Off: Approx. 0.5W Printing: 14.0W <sup>4</sup>	
	665 photos* (CLI-521BK) <sup>3</sup>	Temperature Range	Operating environment: 5°- 35° C	
	*Estimated Supplemental Yield	Humidity	Operating humidity: 10 - 90%RH (no condensation)	
Colour Ink Tank Life	Cyan: 505 pages (CLI-521C), Magenta: 471 pages (CLI-521M), Yellow:505 pages (CLI-521Y) <sup>2</sup>	Acoustic Noise Levels	Printing: Approx. 45.5 dB(A) When printing ISO/JIS-SCID N2 pattern on 10x15cm	
	Cyan: 205 photos (CLI-521C), Magenta: 206 photos		Photo Paper Plus Glossy II using default settings	
Madia Tura	(CLI-521M), Yellow: 211 photos (CLI-521Y) <sup>3</sup>	Dimensions (W x D x H)	431 x 296 x 153mm	
Media Type	Plain Paper, Envelopes, Photo Paper Pro Platinum (PT-101), Photo Paper Pro II (PR-201), Photo Paper Plus	Weight	Approx. 5.7kg	
	Glossy II (PP-201), Photo Paper Plus Semi-gloss	1. Ink droplets can be place	ed with a pitch of 1/9600 inch at minimum.	
	(SG-201), Glossy Photo Paper "Everyday Use" (GP-501), Matte Photo Paper (MP-101), High Resolution Paper	2. Declared yield value in accordance with ISO/IEC 24711. Values obtained by continuous printing.		
	(HR-101N), T-shirt Transfer (TR-301), Photo Stickers	, ,	andard patterns continuously with the default settings of	
Media Input	(PS-101) Rear Tray: Max. 150 sheets	testing paper using Win	testing paper using Windows Vista printer driver in borderless printing mode and	
Heula Input	Cassette: Max. 150 sheets DVD/CD Tray: 1 printable DVD or CD	Declared yield value dete	Windows Vista Home Premium Photo Gallery. Declared yield value determined based on Canon standard method referring to	
Media Size	Rear Tray: A4, B5, A5, Letter, Legal, Envelopes (DL size or		ISO/IEC 24711.	
Ficula Size	Commercial 10), 10 x 15cm, 13 x 18cm, 20 x 25cm)	<ol> <li>When printing ISO/JIS-SCID N2 pattern on A4 size plain paper using default settings.</li> </ol>		
Madia Misiaha	Cassette: A4, B5, A5, Letter		All specifications subject to change without notice.	
Media Weight	Rear Tray: Plain paper: 64 to 105 g/m <sup>2</sup> and supported Canon special media up to 300 g/m <sup>2</sup>	using Canon Photo Pape	Borderless 10x15cm photo lab quality print speed based on Standard driver setting using Canon Photo Paper Plus Glossy II media.	
Two Sided Printing	Cassette: Plain paper: 64 to 105 g/m <sup>2</sup> Automatically selectable using plain paper in A4, B5, A5,	patterns on plain paper.	PPM print speed is based on the highest speed mode setting using Canon standard	
rwo sided Finiting	Letter & sizes		s soon as first page begins to feed into printer and may vary	
Borderless Printing	Yes (A4, 20 x 25cm, 13 x 18cm, Letter, 10 x 15cm)		depending upon a number of factors. Print speed does not take into account data processing time on host computer.	
Interface and software			nding on texts/photos printed, applications software used,	
Interface Type – PC	USB2.0 Hi-Speed		paper used. For yield information see	
Interface Type – Camera	Direct Print Port: Camera direct photo printing from PictBridge compliant digital cameras & camcorders	All brand and product na	www.canon-europe.com/ink/yield All brand and product names are trademarks of their respective companies. Microsoft, Windows and the Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries. For more information on ChromaLife100° please visit	
Interface Type - Mobile Phone / PDA	Photo printing via PictBridge	trademarks of Microsoft		
Supported Operating System	Windows Vista™ (32bit, 64bit) / Windows XP SP2 / Windows 2000 Professional SP4 Mac OS X v.10.3.9 - v.10.5	www.canon-europe.com		
Minimum System Requirements	Windows: PC: Windows Vista™, XP, 2000 Professional / Internet Explorer 6.0 / CD-ROM drive / SVGA Display 800 x 600 Mac OS X v.10.3.9, v.10.4, v.10.5 / Safari / CD-ROM drive /			
	XGA Display 1024x768			