

FS-1300D

A4 MONOCHROME DESKTOP PRINTER

► print ► copy ► scan ► fax

DEPENDABILITY ON YOUR DESKTOP.

The Kyocera FS-1300D is the personal printer you need in busy situations. Dependable and robust, it won't let you down when things get hectic. Fast printing and standard duplex for double-sided printing mean all tasks are handled effectively and economically. High quality output gives your documents the professional edge you're looking for.

- 28 pages per minute with true 1,200 dpi resolution
- Max. paper capacity of up to 800 sheets (incl. options)
- Standard duplex unit for double-sided printing
- Compact design, robust and reliable
- Powerful controller with 32MB RAM as standard
- Long-life components

Product depicted includes optional extras

Less than 6 seconds
first-page-out time
increases productivity.



Input paper from up to
4 sources:

- the standard feeder,
- 2 optional feeders,
- via the multi-purpose tray.



Ecosys

 **KYOCERA**

FS-1300D

MONOCHROME A4 DESKTOP PRINTER



ECOSYS devices are designed to minimise both direct costs, such as consumables and indirect cost, such as maintenance administration. The cartridge-free system requires only the toner to be replaced. The modular design concept allows you to add workflow enhancing functions and a wide variety of paper handling capabilities as required. Integrated system software provides long-term cross-network compatibility. Kyocera's long-life components cost you and the environment less.

System platform:

With the Kyocera page design and control language PRESCRIBE IIe, even complex graphics, logos and forms (including multipart forms) can be created independently of the system and saved and updated in the printer. Consequently, integration into print files no longer applies. They are only accessed as required and therefore relieve the load on the network.

PRESCRIBE IIe:

With the Kyocera page design and control language PRESCRIBE IIe, even complex graphics, logos and forms (including multipart forms) can be created independently of the system and saved and updated in the printer. Consequently, integration into print files no longer applies. They are only accessed as required and therefore relieve the load on the network.

Status Monitor/KM-NET Viewer:

The settings of the FS-1300D can be checked visually and amended from any Windows PC, while the Status Monitor ensures easy setup and checking of the printer status via a USB connection. KM-NET Viewer is an advanced printer management software tool using the standardised protocol SNMP.

GENERAL

Technology: Kyocera ECOSYS, Laser
Engine speed: Up to 28 pages per minute A4
Resolution: 1,200 x 1,200 dpi
Time to first page: 6 seconds or less
Warm-up time: 19 seconds
Duty cycle: Max. 20,000 pages per month, average 2,000 pages per month
Power source: AC 220 ~ 240 V, 50/60 Hz
Power consumption: Printing: 439 W, Stand-by: 8.3 W, Power-Saving (ECOpower): 4.4 W
Noise (ISO 7779): Printing: 53 dB(A), Stand-by: 30 dB(A), Power-Saving (ECOpower): Immeasurably low
Dimensions (W x D x H): Main unit: 375 x 393 x 250 mm
Weight: Main unit incl. toner: Approx. 10 kg
Certifications: TÜV/GS, CE, PTS
This product is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on a paper weight of 80 g/m². Please use paper recommended by Kyocera under normal environmental conditions.

Input capacity: 250-sheet universal paper cassette, 60-120 g/m², A4, A5, A6, B5, Letter, Legal, Custom (105 x 148 mm to 215.9 x 297 mm)
50-sheet multi-purpose tray, 60-220 g/m², A4, A5, A6, B5, Letter, Custom (70 x 148 mm to 215.9 x 356 mm)
Max. input capacity with two optional paper feeders PF-100: 800 sheets
Duplex as standard
Output capacity: 250 sheets face-down

CONTROLLER

Processor: PowerPC 405F5 / 360 MHz
Memory: Standard 32 MB + ECOMemory, max. 544 MB in 1 SDRAM DIMM slot
Emulations: PCL6/PCL5e incl. P.J.L, KPDL 3 (PostScript 3 compatible) with automatic emulation sensing (AES), Line Printer, IBM Proprinter X24E, Epson LQ-850, Diablo 630
Controller language: PRESCRIBE IIe
Fonts: 80 outline fonts accessible in all emulations, 1 bitmap font, 45 types of one-dimensional barcodes plus two-dimensional barcode PDF-417.
Downloadable fonts: Kyocera, PCL + TrueType format, Type 1 + 3 format
Print features: Automatic duplex unit enables pagination printing

INTERFACES

Standard interface: USB 2.0 (Hi-Speed), KUIO-LV interface slot

OPTIONS

Paper handling
PF-100 Paper feeder (max. 2 units): 250 sheets, 60-120 g/m², A4, A5, A6, B5, Letter, Legal, Custom (148 x 210 mm to 215.9 x 356 mm)
CB-100 Cabinet: Wooden desk with storage capacity, including castors (wheels)
Memory
Printer memory: 1 SDRAM DIMM slot (64, 128, 256, 512 MB)
CompactFlash® memory card type 1: 1 slot up to 2 GB, forms, fonts, logos, macro storage

Optional interface
IB-23 Network card: 10Base-T/100Base-TX
SB-110FX Network card: 10Base-T/100Base-TX/100Base-FX, FibreOptic
SB-110 Network card: 10Base-T/100Base-TX

CONSUMABLES

TK-130 Toner-kit: Microfine toner for 7,200 pages in accordance with ISO/IEC 19752*

*Capacity of starter toner is 3,600 pages in accordance with ISO/IEC 19752

WARRANTY

2-year warranty as standard. Kyocera guarantees the drum and developer for 3 years or 100,000 pages (whichever occurs sooner), provided each printer is used and cleaned in accordance with the service instructions.

KYO LIFE Optional 3-year on-site warranty for printer and options.

MODEL CONFIGURATIONS

FS-1300DN: Incl. integrated IB-23 Network card



Select your options to suit your needs:



Product depicted includes optional extras

Your Kyocera Business Partner:

pureprint®



CarbonNeutral® company

Printed by Beacon Press, a CarbonNeutral® company, using proprietary pureprint® environmental print technology.

KYOCERA MITA (UK) Ltd, 8 Beacontree Plaza, Gillette Way, READING RG2 0BS
Tel: 0118 931 1500, Fax: 0118 931 1108, email: info@kyoceramita.co.uk, www.kyoceramita.co.uk

Kyocera does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

