THE COMPACT WORKGROUP COPIERS.

Designed for superb ease of use, the TASKalfa 180 and 220 copiers will help to speed up your office workflow. From the design of the cassette grip all the way up to the intuitive layout of the control panel, these compact copiers are easy to operate, while delivering the professional quality that your business demands

- ▶ Up to 18/22 pages A4 and 8/10 pages A3 per minute
- ► Time to first copy 5.7 seconds or less
- ▶ Optional duplex unit for cost-saving double-sided printing
- ➤ 50-sheet reversing document processor for effortless copying of double-sided originals
- ► 600 dpi laser technology with 256 greyscale copying for crisp text and realistic photos
- ▶ 400-sheet standard paper capacity (expandable to 1,300 sheets)
- Optional GDI printer
- Long-life components provide exceptional efficiency and reliability



The user-friendly display offers quick access to all digital features.

Fill trays less frequently by adding paper capacity of up to 1,300 sheets.









TASKalfa 180/220

MONOCHROME DIGITAL COPIERS FOR A3 FORMAT

The TASKalfa 180/220 incorporate extremely durable components that guarantee efficient and reliable operation to meet the demanding requirements of busy office environments. These devices provide long hardware maintenance cycles that keep your overall operating costs low and productivity high - whilst ensuring a minimum impact on the environment.

Technology

KYOCERA Laser, Mono component

Engine speed

TASKalfa 180: Max.18/8 pages per minute A4/A3 TASKalfa 220: Max. 22/10 pages per minute A4/A3

600 x 600 dpi, 256 grevscales

Warm-up time

17.2 seconds or less from power on

Time to first copy

5.7 seconds or less

Dimensions (W x D x H)

568 x 546 x 502 mm

Weight

Main unit: approx. 33 kg

Power source

AC 220 ~ 240 V, 50/60 Hz

Power consumption

TASKalfa 180: Printing: 424 W - Stand-by: 60 W -

Sleepmode: 2.6 W

TASKalfa 220 Printing: 437 W - Stand-by: 60 W -Sleep mode: 2.6 W

Noise (ISO 7779/9296)

Copying: 65.3/66.7 dB(A) Stand-by: 40 dB(A)

Safety standards

GS, TÜV, CE

This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity

300-sheet universal paper cassette, 64-105 g/m², A3, A4, A5, Ledger, Letter, Legal, Folio

100-sheet multi-purpose tray, 45-160 g/m², A3, A4, A5, A6, Ledger, Letter, Legal, Folio, Custom (98 x 148 mm to 297 x 432 mm)

Max. input capacity with options: 1,300 sheets

Output capacity

250 sheets face-down

Max. original size

Continuous copying

1-999

Memory capacity

Standard 32 MB, max. 160 MB

Zoom range

25-400 % in 1 % steps

Exposure mode

Auto, manual: 5 or 9 steps

Image adjustments

Text + photo, text, photo

Digital features

Scan-once-print-many, electronic sort copy, rotate sort copy*, automatic paper selection, duplex copying**, combined inch/metric copying, layout mode (2-in-1, 4-in-1), ECOcopy mode, program key mode, management mode

*Additional paper feeder PF-420 is required

**Additional duplex unit DU-420 is required

CPU ARM 946-S 150MHz, Flex R1SC

Standard max. 32 MB

Emulations

Host based printing system for all current windows operating systems

Standard Interface

USB 2.0 (Hi-speed)

TK-435 Toner-kit

Microfine toner for 15,000 pages with 6% A4 coverage Capacity of starter toner for 3,000 pages with 6% A4

Printing System (Z)

DP-420 Reversing document processor: 50 sheets, duplex scan, 45–160 g/m², A3-A5R, Folio, Ledger-Statement-R

PF-420 Paper feeder: 300 sheets, 64–105 g/m², A3-A5R, Folio, Ledger-Statement-R (max. three PF-420 can be added to the basis-system)

DU-420 Duplex unit: 64-105 g/m², A3-A5R, Folio, Ledger-Statement-R

Copy memory

DIMM memory: 1 additional slot for 16 MB, 32 MB, 64 MB, 128 MB (max. 160 MB)

Optional interface

IB-110: external network print server

Others

Platen cover (E)

Cabinet: wooden / metal with desk storage capacity

including castors (wheels) CB-420L (low / wooden) CB-420H (high / wooden) CB-421L (low / metal)

CB-421H (high / metal *For high type cabinet max. 2 cassettes can be configured



Your KYOCERA Business Partner:





KYOCERA MITA Europe B.V. – Branch Office Germany – Otto-Hahn-Straße 12 – 40670 Meerbusch – Germany Tel +49 (0) 2159 928-500 – Fax +49 (0) 2159 918-100 www.kyoceramita-europe.com - info@kyoceramita-europe.com

KYOCERA MITA Corporation – 2-28, 1-Chome – Tamatsukuri – Chuo-Ku Osaka 540-8585 – Japan – www.kyoceramita.com

* KYOCERA does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged. KYOcount is a trademark of KYOCERA MITA Europe B.V.