



Business A4 colour and mono printing, giving a competitive advantage to demanding workgroups

The new high performance C5000 Series is the perfect solution for businesses wanting to work more productively, print more professionally and keep a tight control over costs.

No two workgroups have exactly the same print requirements, so the C5000 Series has been designed accordingly. The C5750 model is for workgroups who want high volume, low cost, mono printing with occasional use of colour, whereas the C5950 model is intended specifically for those who print mostly colour. There are also several options including extra trays, double-sided printing and enhanced document security.

Both models offer a harmonious combination of hardware, consumables and in-box software, as well as PCL/PostScript as standard. This enables printing from a greater range of applications and easier printing of PDF's.

The C5000 Series. Printers with the performance to match the need.

The fastest, most professional business printers.

- Class-leading print speeds of 32 pages per minute (ppm) mono and up to 26 ppm colour.
- Fast time to first print at just 8 seconds for a mono page or 11 seconds for colour.
- ProQ2400 Multi-level technology and High Definition Toner together give a better level of detail, greater colour depth, reduced grain and a high gloss feel
- Graphic Pro colour management provides the tools to download colour profiles to the printer's hard disk for specific colour matching

Extend the possibilities of in-house printing.

- 64-203gsm paper support in sizes A6-A4 and 1.2m banners
- Free in-box Template Manager software allows creative in-house printing
- Automatic duplex printing available for professional double-sided printing, enabling booklet printing, reduced paper use and space saving.
- Input capacity of up to 930 sheets allows non-stop printing without user intervention.

Enjoy colour. Take control.

- Print Control enables the management of colour use and printing costs of each individual user
- Users are able to print confidential documents with ease due to helpful functionality, such as password protection

Designed for easy operation by all.

- Easy to change consumables, with a helpful gauge on the LCD panel clearly showing toner levels
- High capacity mono toner cartridges reduce running costs and user intervention
- Mono running costs are equivalent to many mono only products
- Auto Colour Balance ensures consistent results throughout the life of the printer.
- Photo Enhance provides stunning photo-like quality on ordinary office paper.

THE C5750 & C5950 FEATURES AT A GLANCE

	C5750n	C5750dn	C5950n	C5950dn	C5950dtn	C5900cdtn
Colour speed (A4)	22ppm		26ppm			
Mono speed (A4)	32ppm					
Printer language	PCL/PostScript					
Print quality	ProQ2400 Multi-level technology & High Definition Toner					
Memory	256MB					
10/100 networking	•					
Duplex (for double-sided printing)	○	•	○	•	•	•
2nd paper tray (for 930 sheet max paper capacity)	○			•		
Cabinet	○			•		
Hard Disk Drive	○ 40GB					

• Standard ○ Optional



The C5750 & C5950 Colour and Mono Printers

	C5750n	C5750dn	C5950n	C5950dn	C5950dtn	C5950cdtn
Order number	01212701	01212801	01213101	01213201	01213301	01213401
Speed & throughput	A4 Print speed	22ppm colour, 32ppm mono		26ppm colour, 32ppm mono		
	Time to first print	8 seconds mono, 11 seconds colour		8 seconds mono, 9 seconds colour		
	Warm up time	up to 60 seconds from power on & up to 45 seconds from power save				
	Processor speed	500MHz				
Print quality	Resolution	ProQ2400 Multi-level technology, 1200 x 600dpi				
	Enhancements	Auto Colour Balance, Photo Enhance via driver (excludes Mac and PostScript drivers)				
Typefaces	Printer fonts	Scalable: 87 PCL fonts and 136 PostScript fonts; PCL Bitmap fonts. OCR-A/B; USPS ZIP Barcode				
Compatibility	Printer languages	PCL 6 (XL3.0) and PCL5c, PostScript 3 (clone). SIDM (IBM-PPR, EPSON-FX)		PCL 6 (XL3.0) and PCL5c, PostScript 3 (clone). SIDM (IBM-PPR, EPSON-FX), PDF Direct Print v1.5		
	Connectivity	Hi-Speed USB, 10/100-TX Ethernet & IEEE 1284 Bi-directional Parallel				
	OS Compatibility	Windows 2000 / XP Home / XP Professional / XP Professional x64 / Server 2003 / Server 2003 for x64 / Vista (32-bit) / Vista (64-bit) / Mac OS X PowerPC 10.2.8 or greater / Mac OS X Intel 10.4.4 or greater ¹				
	Barcode Support	Barcode with Checksum support				
Utility Suite	Color Correct, Oki LPR (Windows only), PrintSuperVision.net (Windows only), Swatch Utility, Template Manager 2006 (Windows only), Web Driver Installer (Windows only), WebPrint (Windows only), Print Control Server (Windows only), Print Control Client, Storage Device Manager ² (Windows only), Gamma Utility, Profile Assistant ²					
Memory	Std RAM	256MB				
	Max RAM	768MB				
	Hard Disk Drive	40GB (Optional)				
Paper handling	Paper capacity tray 1	300 sheets of 80gsm. Paper sizes: A4, A5, B5, A6				
	Paper capacity optional 2nd tray	530 sheets of 80gsm. Paper sizes: A4, A5, B5,				
	Paper capacity of multi-purpose tray	100 sheets of 80gsm. Paper sizes: A4, A5, B5, A6, 10 Envelopes (Com-9, Com-10, DL, Monarch, C5), Labels (Avery 7162, 7664, 7666), Custom Size (up to 1200mm length including Banner), 50 transparencies				
	Standard tray paper weight	64 – 120gsm				
	Optional 2nd tray paper weight	64 – 176gsm				
	Multi-purpose tray paper weight	75 – 203gsm				
	Duplex	Optional	Standard	Optional	Standard	
	Duplex paper sizes	Supported paper sizes: A4, A5, B5. Supports Custom Size: Width 148 – 215.9mm Length 210 – 355.6mm				
	Duplex paper weight	75 – 105gsm				
	Paper output	250 sheets face down, 100 sheets face up, 80gsm				
Operating conditions	Temperature/Humidity	10°C to 32°C (17°C to 27°C recommended) / 20% to 80% RH (50% to 70% RH recommended)				
	Storage	-10°C to 43°C, 10% to 90% RH				
Power requirements	Power supply	Single phase 220–240VAC, frequency 50/60Hz +/-2%				
	Power consumption	Typical 490W, Peak 1200W, Idle 100W (average), Power save <17W				
Noise level	Operating: Up to 55.6 dB(A), Standby: 37 dB(A), Power Save: Background Level					
Dimensions (HxWxD)	339.5mm x 400mm (max 435mm) x 528mm (max 563.5mm)	339.5mm x 400mm (max 435mm) x 621mm	339.5mm x 400mm (max 435mm) x 528mm (max 563.5mm)	339.5mm x 400mm (max 435mm) x 621mm	486.5mm x 400mm (max 435mm) x 621mm	911.5 x 400mm (max 533mm) x 621mm
Weight³	Approx 26kg	Approx 29kg	Approx 26kg	Approx 29kg	Approx 36kg	Approx 51kg
Duty cycle	Printer duty (max)	60,000 pages/month				
	Printer duty (average)	1,500 – 5,000 pages/month				
Warranty	Pan European 1 year on-site					
Accessories	Duplex	Optional (43347502)	Standard	Optional (43347502)	Standard	
	Memory	256MB (01182901) or 512MB (01182902)				
	2nd tray	Optional (43347602)			Standard	
	Hard Disk Drive	40GB (01184501)				
	Cabinet	Optional (09004619)				Standard

¹ Check local OKI Printing Solutions website for latest driver releases & OS compatibility.

² Hard Disk Drive required.

³ Includes all consumables.

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI Printing Solutions toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible," and if it does work, your printer's performance and print quality may be degraded.

Description	Life* (pages)	Order Numbers					
Black toner	8,000	43865708		43865724			
Colour toners	2,000	Cyan: 43872307 / Magenta: 43872306 / Yellow: 43872305		N/A			
	6,000	N/A		Cyan: 43865723 / Magenta: 43865722 / Yellow: 43865721			
Image drum	20,000 A4 pages @ 3 pages/job	Black: 43870008 Cyan: 43870007 Magenta: 43870006 Yellow: 43870005		Black: 43870024	Cyan: 43870023	Magenta: 43870022	Yellow: 43870021
Transfer belt	60,000 A4 pages @ 3 pages/job	43363402					
Fuser unit	60,000 @ A4	43853103					

*All toners: A4 pages @ 5%, Printer shipped with 2250 pages @ 5%. All Drums: A4 pages average life. Specification subject to change without notice. All trademarks acknowledged.

OKI EUROPE LTD.
 Central House, Balfour Road
 Hounslow, Middlesex TW3 1HY
 United Kingdom
 T +44(0) 20 8219 2190
 F +44(0) 20 8219 2199
WWW.OKIPRINTINGSOLUTIONS.COM

