

# ML3390/ML3391 DOT MATRIX PRINTER



- ❖ ML3390
- ❖ ML3391
- ❖ 24-PIN DOT MATRIX PRINTER

## A VERSATILE FORM PRINTER WITH 24-PIN PRINT HEAD FOR IMPROVED PRINT QUALITY

The ML3390/ML3391 narrow and wide carriage printers offer excellent flexibility to users who rely on one printer to perform a wide variety of tasks. Easy to use, highly reliable and with very low running costs, the ML3390/ML3391 are ideal for retail, small business and office applications.

## MAIN FEATURES OF THE ML3390/ML3391 PRINTER

- ❖ 80/136 column dot matrix printers
- ❖ 24-pin print head with Oki reliability
- ❖ Up to 390 characters per second print speed
- ❖ Multi-part paper-handling (original + 4 copies)
- ❖ Ideal for general use and printing of invoices, statements, management Information etc.



# OKI

# ML3390/ML3391 DOT MATRIX PRINTER

## PRODUCT SPECIFICATION

		ML3390	ML3391
<b>General</b>	Number of pins	24	
	No. of multi-part forms	5 (one original + 4 copies)	
<b>Speed &amp; throughput</b>	Utility (12cpi & 10cpi)	312cps; 260cps	
	Letter quality (12cpi & 10cpi)	104cps; 87cps	
	Fastest print speed	390cps	
<b>Font &amp; print features</b>	Carriage width (10cpi)	80 columns	136 columns
	Max. in compressed mode	160 columns	272 columns
	Character pitch	10/12/15/17.1/20 pitch & proportional	
	Graphics resolution	Up to 360 x 360 dpi	
	Typeface & Font	Courier (Scalable), Roman (Scalable), Swiss (Scalable), Prestige, Gothic, Swiss Bold, Utility, Orator, OCR-A, OCR-B + Barcodes	
	Typestyle	Emphasised, Enhanced, Double Width, Double Height, Italics, Outline, Shadow, Bold, Underline, Subscript, Superscript	
<b>Emulations &amp; interfaces</b>	Printer emulations	Epson LQ Esc/P2, IBM ProPrinter X24/XL24	
	Standard interfaces	Centronics Parallel + USB	
	Optional interfaces	Serial RS 232C , Serial RS 422A, Current Loop RS 232C	
<b>Paper-handling</b>	Continuous paper	76–254	76–406mm
	Continuous envelope	165 x 91mm	239 x 102mm
	First printable line (from top of page)	0.5mm	
	Standard	Rear push tractors, Paper parking, Low tear-off, Autoload single sheet	
	Optional	Pull tractor, Single/dual bin cut-sheet feeder, Roll paper stand (ML3390 only), Bottom tractors with metal, Long-life tear-off bar	
<b>Physical</b>	Dimensions (HxWxD)	116 x 398 x 345mm	116 x 552 x 345mm
	Weight	6.9kg	8.9kg
	Memory	128KB	
	Noise level	54dB(A)/50dB(A) (quiet mode)	
<b>Power</b>	Power requirements	230V AC	
	Frequency	50/60Hz	
<b>Reliability</b>	Print head life	200 million characters	
	Ribbon life	2 million characters in utility mode at 10cpi (re-inking cartridge)	
<b>Supplies life</b>	MTBF	10,000 hours	

# OKI

*Ok!, Network Solutions  
for a Global Society*

OKI SYSTEMS (UK) LTD, PART OF OKI ELECTRIC

OKI SYSTEMS (UK) LTD,  
550 DUNDEE ROAD,  
SLOUGH, BERKSHIRE  
SL1 4LE  
UNITED KINGDOM

TEL: +44 (0)1753 819819  
FAX: +44 (0)1753 819899

[WWW.OKI.CO.UK](http://WWW.OKI.CO.UK)

Only use genuine Ok! Original consumables to ensure the best quality and performance from your hardware. Non Ok! Original products may damage your printer's performance and invalidate your warranty. Specifications subject to change without notice. All trademarks acknowledged.



As an ENERGY STAR Partner, Ok! Europe Ltd has determined that this product meets the ENERGY STAR guidelines for energy efficiency

09400924  
© 2003 Ok! Europe Ltd.